

Design and Manufactures of... Flexible Pouch Packaging Machines

Canflex offers a complete range of Packaging Machines for Solid, Liquid and Viscous, Food or Non-Food Products.

IBS-400

Intermittent Static Band Sealer



CANFLEX ENGINEERING PVT. LTD.

P.B. No. 1919, D. No. 7-2-C8/A & C33/A, Industrial Estate, Sanathnagar, Hyderabad - 500018, T.S. INDIA.

Fax: +(91)-40 23813884

Tel: +(91)-40 23712233, 23716699, 98486-22825

Email: info@cannonindia.com Website: canflexindia.com

IBS-400

Technical Specifications

Description: To seal any Multi Layered Laminated Premade Pouches, Pre made pouch film thickness up to 200 microns can be sealed by heavy duty Sealing Bars. Produces strong reliable seals up to 20mm.

01. Pouch Feeding : Horizontal Conveyor

02. Production Speed : Up to 30 pouches/minute

03. Machine Control system : Timer & VFD control

04. Sealing Width : Up to 20mm

05. Film Thickness : 80 to 200 Microns

06. Film Material : laminated/Co-Extruded Virgin Films

07. Sealer Heating System : PID Controller
08. Pouch Width : Up to 400mm
09. Pouch Length : Up to 600mm

10. Compressed Air Pressure : 6.5 Kg/cm at 40c

11. Air Consumption : CFM

12. Power Consumption : 1KW/Hour

13. Peak Power : 1.5KW

14. Power Requirement : 220 V, Single Phase

15. Machine Dimensions in 'mm' : 1370(H) x 2150(W) x 740(Depth)

16. Net Weight : 250kgs (approx)

Note: Due to R&D and products enhancements technical data are subject to change without prior notice.

Technical **Diagram**

CANFLEX ENGINEERING PVT. LTD.