

**CANFLEX**<sup>®</sup>  
(Formerly Known as CANNON)

“ Design and Manufactures of...  
Flexible Pouch Packaging Machines ”

Canflex offers a complete range of Packaging Machines for Powders,  
Granules, Liquids, Viscous & Non-Viscous & all FMCG Products.

## 10-IC-G CUP FILLER



### CANFLEX ENGINEERING PVT. LTD.

P.B. No. 1919, D. No. 7-2-C8/A & C33/A, Industrial Estate,  
Sanathnagar, Hyderabad - 500018, T.S., INDIA.

Tel: +(91)-40 23712233, 23716699, 98486-22825  
Fax: +(91)-40 23813884

Email: [info@cannonindia.com](mailto:info@cannonindia.com)

Website: [www.cannonindia.com](http://www.cannonindia.com)  
[www.canflexindia.com](http://www.canflexindia.com)

**Application:** Grains, Pulses, Seeds, Sugar, Rice, Detergent, Millets, Pop Corn Etc.,

**Description:** Fully automatic mechanically operated vertical pouch form fill & seal machine to pack products like "Granules" in any heat sealable laminated poly pouches with volume adjustment cup filling system. Machine supported on angular structure wrapped with stainless steel cabinet all contact parts are in stainless steel with photo cell operation

01. Feeding head	: Volumetric cup filling system	13. Pouch Length	: Up to 200 mm
02. Production Speed	: 35 to 40 pouches per minute	14. Power Consumption	: 1 kW / Hour
03. Machine control system	: PLC control system	15. Air Consumption	: 2cfm for Batch Cutter / Batch Coding
04. Packing range	: Up to 1Kg	16. Air Pressure	: 5kg cm
05. Film Width	: Up to 420 mm	17. Peak Power	: 3 kW
06. Film Thickness	: 70 to 100 microns	18. Power requirement	: Single Phase, 415 V, 50Hz, + Neutral.
07. Film Material	: Any heat sealable laminated	19. Pouch Counter	: Provided
08. Sealer heating system	: Continues only	20. Film Guard mechanism	: Auto stop when film is exhausted
09. Inner Core Dia. of Film Roll	: 70mm	21. Pouch counter	: Provided
10. Outer Dia. of the film Roll	: Up to 350mm	22. Date printing Device	: Optional
11. Pouch Style	: Centre seal pillow pouches	23. Machine Dimensions	: 1500 (H) x 1100(W) x 1300(Depth)
12. Pouch Width	: Up to 135mm	24. Net Weight	: 600 kgs (approx)

**Note:** Due to R&D and products enhancements technical data are subject to change without prior notice.

Technical Diagram

## CANFLEX ENGINEERING PVT. LTD.

P.B. No. 1919, D. No. 7-2-C8/A & C33/A, Industrial Estate,  
Sanathnagar, Hyderabad - 500018, T.S., INDIA.

Tel: +(91)-40 23712233, 23716699, 98486-22825  
Fax: +(91)-40 23813884

Email: [info@cannonindia.com](mailto:info@cannonindia.com)  
Website: [www.cannonindia.com](http://www.cannonindia.com)  
[www.canflexindia.com](http://www.canflexindia.com)