

Design and Manufactures of... Flexible Pouch Packaging Machines

Canflex offers a complete range of Packaging Machines for Powders, Granules, Liquids, Viscous & Non-Viscous & all FMCG Products.

10 MW MULTI HEAD WEIGH FILLER



CANFLEX ENGINEERING PVT. LTD.

P.B. No. 1919, D. No. 7-2-C8/A & C33/A, Industrial Estate, Sanathnagar, Hyderabad - 500018, T.S., INDIA.

Tel: +(91)-40 23712233, 23716699, 98486-22825 Fax: +(91)-40 23813884

Website: www.cannonindia.com www.canflexindia.com

Email: info@cannonindia.com

Application: Free Flow uneven Crispy products Like Potato Chips, Flakes, Namkeenis, Corn,

Description: Mechanically operated fully automatic form fill & seal machine to pack ©Free Flow uneven Crispy products Like Potato Chips, Flakes, Namkeen is, Dry foods Chocolates & Candies with multi head electronic load cell based weigh metric combination weigh filler. (14 stations) fabricated with heavy duty angular structure weigher supported on channel platform, all contacts parts made out with SS, Machine is controlled by HMI touch screen panel with Photo cell Inclusive.

01. Feeding System : 10 head Multi head combination weigher

02. Production Speed : 25-40 Pouches per min (Depends on Range)

: P.L.C (Programmed Logic Controller) touch screen 03. Machine control system

04. Packing range : 50,100, 200, 500 grams & 1Kg

05. Film Width : Up to 450mm 06. Film Thickness : 70 - 100 microns

07. Film Material : Any heat sealable Laminated

08. Sealer heating system : Continues 09. Inner Core Dia. of Film Roll: 70mm

10: Outer Dia. of the film Roll : Up to 350mm

11: Pouch Style : Center seal pillow pouches

: Up to 210mm 12: Pouch Width

13. Pouch Length : Up to 300mm

14. Pneumatic air : 15cfm@7 kg/cm2 (5hp. air compressor)

15. Power Consumption : 1 kW / Hour 16. Peak Power : 6 kW

17. Power requirement : 3 Phase, 415 V, 50Hz plus Neutral 18. Film Guard mechanism : Auto stop when film is exhausted

19. Pouch Counter : Provided 20. Date printing Device : Optional 21. Photo Cell : Provided

22: Machine Dimensions in "mm" : 1500(H) x 1100(W) x 1300(Depth)

23: Net Weight : 600kgs (approx)


Note: Due to R&D and products enhancements technical data are subject to change without prior notice.

Fechnical **Diagram**

Front View

ELECTRICAL PANEI WIDTH

Side View



CANFLEX ENGINEERING PVT. LTD.

Tel: +(91)-40 23712233, 23716699, 98486-22825

Fax: +(91)-40 23813884